

ALL ELECTRIC SCISSOR LIFTS

# 0608ME All (1932ME All)

Compliant with CE/ANSI/CSA standards

## PRODUCT HIGHLIGHTS

### Hydraulic Oil Free & Environment-friendly

- Zero hydraulic components used makes machine hydraulic oil free, clean operation with zero risk of hydraulic oil leak in job sites
- Zero emissions, low noise and environment-friendly, ideal for stringent working environment such as data center, dust-free workshop and hospital etc

### High Efficiency

- Replacing hydraulic cylinders with electric cylinders, consumes less energy and runs for longer time, greatly improving work efficiency
- Side forklift pockets design makes it flexible and greatly improves transfer and transportation efficiency

### Low Cost for Maintenance & Operation

- Universal components from E-drive slab scissors are used on this machine decreases total cost of ownership
- AC brushless drive motor and AGM maintenance free batteries come as standard
- Unique bumper rails will protect decals and paint well making machine look like new



#### Standard Features

2WD×2WS	Maintenance-free battery	Fault diagnosis system
Solid non-marking tires	Proportional control	Emergency lowering system
Emergency stop system	Electrophoretic painting	Tilt protection system
Flashing beacon	Side/rear forklift pockets	Lifting and tie down points
Foldable guardrail	Automatic pothole protection	Overload sensing system
Drivable at full height	Bumper rails	Manual storage box
Horn & buzzer	AC power to platform	Auto braking system
AC drive motor	Full size swing gate	Telematics-ready connector

#### Options & Accessories

RCBO	Platform work light	Overhead anti-collision device
Footswitch		

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

# ALL ELECTRIC SCISSOR LIFTS 0608ME All (1932ME All)

Compliant with CE/ANSI/CSA standards

Model	0608ME All (1932ME All)
<b>Dimensions</b>	
Max Working Height (Indoor/Outdoor)	5.8 m (19')
A Max Platform Height (Indoor/Outdoor)	7.8 m (25'7")
B Platform Extension	0.9 m (3')
C Length-Stowed	1.8 m (5'11")
D Machine Width	0.81 m (2'7.9")
E Height-Stowed (Rails Folded)	2.14 m (7')
E Height-stowed (Rails Unfolded)	1.88 m (6'2")
F Wheelbase	1.334 m (4'4")
Ground Clearance (Pothole Guard Stowed)	0.061 m (2.4")
Ground Clearance (Pothole Guard Deployed)	0.024 m (0.95")
Platform Size (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")
<b>Performance</b>	
Platform Capacity	230 kg (507 lbs)
Extension Deck Capacity	120 kg (265 lbs)
Max Platform Occupants (Indoor/Outdoor)	2 / 1
Drive Speed (Stowed)	4 km/h (2.5 mph)
Drive Speed (Raised)	0.5 km/ h (0.3 mph)
Lift Time (Unloaded)	25 s~30 s
Lower Time (Unloaded)	25 s~30 s
Gradeability	25%
Max Allowable Inclination(Front-to-Back/Side-to-Side)	3°/1.5°
Turning Radius (Inside/Outside)	0 m/1.62 m (0 /5'3.78")
Tire Spec/Type	323×100mm (12.7×4")/solid non-marking tires
<b>Power</b>	
Drive × Steer	2 WD×2 WS
Drive Motor (V/kW)	24V AC /0.6 kW
Battery Capacity	24V, 220 Ah (AGM Batteries)
Charger (Input/Output)	100~240V AC/30A
<b>Weight</b>	
Weight (Indoor/Outdoor)	1,600 kg (3,527 lbs)
Standards Compliance	CE/ANSI/CSA

